

PRODUCT DESCRIPTION

Nerolac Beauty Gold is a specially formulated emulsion paint based on a durable copolymer resin, high opacity, micronised pigments, and additives to give better, beautifying and stain resistance properties.

PERFORMANCE FEATURES & BENEFITS



RECOMMENDED USAGE

It is recommended for interior application to a wide variety of new or previously painted surfaces such as plaster, brickwork, cement rendering, concrete, hardboard, building boards, etc. It can be applied on ceiling and wall surfaces where a man finish, free from irritating glares due to light reflection, is desired.

RECOMMENDED SYSTEM FOR APPLICATION

For New Masonry Surfaces

- 1 Interior Primer** (1 Coat) Dry in 4 6 hrs
- 2 Acrylic Wall Putty## (1 Coat) Dry in 6 8 hrs
- 3 Interior Primer** (1 Coat) Dry in 4 6 hrs
- Finish Nerolac Beauty Gold Acrylic Plastic Emulsion (2 3 coats) Dry min. 4 6 hrs. in between coats.

SURFACE PREPARATION

- 1 Ensure the surface is clean, dry, free from all defective or poorly adhering material, din, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down, using suitable abrasive paper and thereafter wipe off
- Apply a coat of suitable Nerolac Interior Primer Sealer followed by Nerolac Wall Putty to level the dams and make the surface uniform.
- Apply again a coat of suitable Nerolac Interior Primer Sealer.
- Then apply two to three coats of Nerolac Beauty Gold Acrylic Plastic Emulsion.

TECHNICAL DATA



COVERAGE**

140 - 160 sq. ft / ltr / coat.





DRYING TIME

Surface Dry: 30 Minutes





RECOATING

Min. 4 - 6 hrs. (@27° \pm 2°C & RH 60 \pm 5%)






GL Sh

GLOSS LEVEL

Sheen





20 - 25 : Brush 35 - 40 : Roller





voc

< 50 gm/ltr.





"*Actual coverage may vary depending on Method, Condition of Application, Type of Tools, Surface Porosity & Shade. Use of Felt Roller may reduce coverage upto 50%.

PRECAUTIONS

- 01) Refer MSDS for "Nerolac Beauty Premium Acrylic Emulsion Washable Smooth Finish" for safety measures & precautions.
- 02) Store in well-ambient conditions, ventilated locations & away from sources of ignition and fire.
- 03) Keep away from children.
- 04) In case of eye / skin contact, wash with plenty of water.
- A
- 05) Inhalation / Injection can be dangerous. In either case, move to fresh air & consult medical practitioners.
- 06) Do not apply when ambient temperature might drop to levels below 100 within 4 hrs of application.
- 07) New plaster should be allowed to cure for minimum 12 weeks.
- 08) Avoid extra thinning for better results.
- 09) Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir the tinted paint well, after tinting & before application.
- 10) The container must be tightly closed when not in use. Stir well and strain before use.
- 11) Use safety equipments like rubber or polythene gloves, safety goggles / glasses & face mask.

SAFETY FEATURES:

Surfaces painted with Nerolac Beauty Gold Premium Finish Washable Smooth Finish are washable by sponging with mild soap and water after a minimum of 2 weeks drying to remove ordinary stains and everyday dirt.

SAFETY FEATURES:





COLOR:

As per Beauty Gold Shade Card & Colour Scapes Fandeck.

NO. OF SHADES POSSIBLE: More than 1450

