



NEROLAC

IMPRESSIONS

METALLIC FINISH (INTERIOR & EXTERIOR)

PRODUCT DESCRIPTION

Nerolac Impressions Metallic Finish Wall Emulsion is a premium-quality, special effect designer series range that creates a variety of special effects and textures on interior walls and is based on pure acrylic emulsion.

PERFORMANCE FEATURES & BENEFITS



RECOMMENDED USAGE

Nerolac Impressions Metallic Finish Wall Emulsion can be applied on the interior & exterior surfaces, on new previously painted surfaces such as plaster, brickwork, cement rendering, concrete, hardboard, building boards, etc.

RECOMMENDED SYSTEM FOR APPLICATION

For New Masonry Surfaces

- 1** Interior or Exterior Primer** (1 Coat) Dry in 4 - 6 hrs.
- 2** Acrylic Wall Putty or All Purpose Putty## (1 Coat) Dry in 6 - 8 hrs.
- 3** Interior or Exterior Primer** (1 Coat) Dry in 4 - 6 hrs.
- 4** Finish coat (1 Coat) Nerolac Impressions Metallic Finish.

Sand the surface with emery paper and wipe clean before application of subsequent coat.

**Nerolac Interior Primer (waterthinnable).

##Nerolac Acrylic Wall Putty.

#Minimum 4-6 hrs for Water Thinnable Primer.

SURFACE PREPARATION

- 1** Ensure the surface is clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc. Remove all loose or poorly adhering materials by rubbing down, using suitable abrasive paper and thereafter wipe off.
- 2** Apply a coat of suitable Nerolac Interior Primer Sealer followed by Nerolac Wall Putty to level the surface and make the surface uniform.
- 3** Apply again a coat of suitable Nerolac Interior Primer Sealer.
- 4** Then apply two to three coats of Nerolac Beauty Premium Acrylic Emulsion Washable Smooth Finish.
- 5** Treat fungus affected areas using Nerolac Fungicidal Solution and allow it to react for 6 - 8 hrs.



TECHNICAL DATA



COVERAGE**

140 - 160 sq. mt/ltr/coat when applied to smooth and non-absorbent surface (by felt roller).



DRYING TIME

Surface Dry : 60 - 90 Minutes



RECOATING

Min. 4 - 6 hrs. (@27°± 2°C & RH 60 ± 5%)



GLOSS LEVEL

Sheen



THINNING

Max 5% by volume using water



FLASH POINT

NA



STABILITY OF THINNED PAINT

Use within 24 hrs



WASHABLE

Moderate

**Actual coverage may vary depending on Method, Condition of Application, Type of Tools, Surface Porosity & Shade. Use of Felt Roller may reduce coverage upto 50%.

PRECAUTIONS



1. Refer MSDS for "Nerolac Impressions Metallic Finish Wall Emulsion" for safety measures & precautions.
2. Store in well-ambient conditions, ventilated locations & away from sources of ignition and fire.
3. Keep away from children.
4. In case of eye/skin contact wash with plenty of water.
5. Inhalation/Injection can be dangerous. In either case, move to fresh air & consult medical practitioners.
6. Do not apply when ambient temperature might drop to levels below 10°C within 4 - 5 hrs of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. The container must be tightly closed when not in use. Stir well before use.
10. Use safety equipment like rubber or polythene gloves, safety goggles/glasses & face masks.

SAFETY FEATURES:

Surfaces painted with Impressions Metallic Finish are washable by sponging with mild soap and water after a minimum of 2 weeks drying to remove ordinary stains and everyday dirt.

SAFETY FEATURES:



Non-Flammable.

PACK SIZES:



200 ml & 0.90 Ltr.

COLOR:

Gold & Silver.

